# **PRODUCT INFORMATION**



www.growtex.com.au sales@growtex.com.au 1300 902 285

# **Crop Remover Compact 65**

<u>Model</u> <u>Revision</u>

Crop Remover Compact 65 00 – 02052020



## Motor

Doosan industrial engine D18 stage 5 +/- 45 kw.

# Benefits of this engine:

- Low fuel consumption.
- Worldwide service network.
- Simple and effective operation.



## **Operator/Driving force**

Hydraulic drive of conveyor and cloth roll. The machine is equipped with **1** LS pump and Danfoss hydraulics. The pump is assembled directly on the flywheel of the engine.

#### Benefits:

- Directly driven pumps ensure a compact construction and no maintenance costs.
- Danfoss hydraulic control valves for proper and smooth operation of the machine.

#### Infeed table

Importation table with on both sides a roll-up unit for cloth up to 200 meters. Operation only on one side at a time. High ridges on the elevator belt will rise up for the good upwards conveying of the product.



## **Control panel**

Remote control of the machine, system Hetronic.

#### Benefits:

- Operation is always possible from the place with the most visibility and is therefore safe.
- The machine is operated by remote control, allowing you to stay out of the danger zone of the machine.
- Hetronic is known worldwide, highly durable and trouble-free.



#### Chassis

VTS undercarriage with rubber tracks.



### **Dimensions**

Machine dimensions approximate:

- Width caterpillar's exterior frame about 2.1 meters.
- Width 2.1 meters.
- Height 1.9 meters.
- Length 3.9 meters.
- Weight +/- 3.500 kg.
- Canvas width up to 1400 mm.

# Capacity

Up to 8.000 m<sup>2</sup> per hour.

# **Optional**

- Bunker container 15 m<sup>3</sup>.
- Automatic lubrication system.